

Helix Load Control Indicator

3.5 minutes at 134°C /
4 minutes at 132°C

- Conforms to EN ISO 11140–1 Class 6
- Class 2 indicator for specific use
- Indicator using Class 6 diagnostic technology
- Effective Load release
- Compliments your in-packing monitoring
- Self-adhesive backing for documentation purposes
- Easy to use - Easy to interpret
- Non-toxic / Lead free



The Parasure 3.5 min at 134°C / 4 min at 132°C Load Control is designed to be used in conjunction with the Parasure in pack monitoring systems.

- Placed in the chamber with the load and read on completion of the cycle it provides immediate physical independent confirmation that the cycle parameters have been met in the chamber - for confident release of the load.

Order Details

PS1410


3.5 min / 4 min Load Control
Device & 250 Indicators

TECHNICAL SPECIFICATIONS

Name:	3.5 min Load Control
Classification:	EN867 Part 5
Operating temp:	134°C / 132°C
Time:	3.5 min / 4 min
Storage conditions:	10°C - 30°C
RH:	30 - 70%
Lot no.	yes, on the indicator
Prod date:	yes, on the box
Indicator:	yes in accordance with EN-ISO 11140-1 (class2)
Disp/single use:	250 cycles
Extra information:	
Coated	yes
Non-toxic/Lead free	yes
Lot no.	yes
Recordable Information:	
Pass/fail result	yes
Colour change	blue to black

Helix Load Control

3.5 minutes at 134°C
4 minutes at 132°C



Before

Original Indicator



After

After total process



Address: Squirrels | Kithurst Park |
Storrington | West Sussex | RH20 4JH | England |
Tel: +44 (0) 1903 741390

Warehouse Address: Units B10/B11
Oakendene Estate | Bolney Road | Cowfold |
West Sussex | RH13 8AZ | England